

Concrete Release Agent **FRE-FORM**

TECHNICAL DATA

1.0 DESCRIPTION

FRE-FORM concrete release agent is a chemically active form release agent designed specially for use with steel forms, steam curing and general formwork.

FRE-FORM is suitable for use on all forms except expanded polystyrene. Properly applied, FRE-FORM will not interfere with the adhesion of coatings and sealants. Prior to painting or applying coatings, wash the surface with water containing a little detergent and brush down thoroughly.

A further characteristic of FRE-FORM is that it affords protection to the formwork itself by, in the case of steel, inhibiting rust, and in the case of timber, impregnating the timber rendering it water repellent.

2.0 PHYSICAL PROPERTIES:

2.1. Colour	Amber
2.2. Specific Gravity	0.84
2.3. Flash Point	>100°C
2.4. Shelf Life	1 year in original sealed container.
2.5. Viscosity	thin (sprayable).
2.6. D.G. Classification	9 (Ecotoxic), UN 3082
2.7. Toxicity	Contains Diesel – avoid skin contact. Refer SDS.
2.8. Coverage	
	Non-absorbent surfaces (e.g., steel, fibreglass): up to 20m ² per litre
	Absorbent surfaces (e.g., wood, concrete, uncoated plywood) up to 15m ² per litre.

3.0 USES

FRE-FORM is effective on all types of moulds and formwork. FRE-FORM is recommended for steam-cured metal formwork.

FRE-FORM promotes easy stripping, minimises form clean up, is non-staining and reduces the number of surface air voids (bugholes). Refer precautions.

For tilt-slab construction, use DISCRETE. Refer DISCRETE data sheet.

4.0 APPLICATION INSTRUCTIONS

- 4.1. Use only in a well-ventilated area. Avoid skin contact and do not breathe vapours/mists.
- 4.2. Surfaces to be treated must be clean and free of all water, dust and dirt or residues (including any cleaning agents or other release agents) that might transfer to the final concrete surface.
- 4.3. For greatest coverage and best results, apply with a soft, clean cloth taking care to eliminate excess material. Alternatively spray-apply in the form of small droplets (do not atomise), and then wipe up any excess with a soft cloth. Ensure application of FRE-FORM is consistent across the formwork.

FRE-FORM

TECHNICAL DATA Continued

4.0 APPLICATION INSTRUCTIONS (continued)

4.4. DO NOT OVER APPLY. DO NOT APPLY TO REINFORCING STEEL.

4.5. FRE-FORM must be applied to the formwork prior to each use.

5.0 PRECAUTIONS

Read labels before use.

For non-standard concrete mixes, including those with special admixtures, pigments and other additives, test for release properties and final appearance.

Marks (including polishing or cleaning marks on steel forms, dents, etc), contamination, etc present on the form may show on the concrete surface once the concrete is released. Ensure the formwork is clean and free from contamination and surface defects before use and between uses.

DO NOT over apply. Over application may cause adverse effects to the concrete surface. Wipe up any puddles or excess material.

Refer to Material Safety Data Sheet for handling and first aid information. Wear protective gloves and eye protection when applying and do not breathe vapours or mists. Use only in a well-ventilated area.

6.0 PACKAGING

FRE-FORM is available in 20 and 210 litre containers.



Leading solutions for construction.

The information contained in this data sheet, is to the best of our knowledge accurate and any recommendations or suggestions which may be made are without liability on our part, since the conditions of use are beyond our control. Users are urged to make their own assessment of our products under their own conditions and for their own requirements. Stratmore Construction Solutions Limited reserves the right to alter formulations without notice. Properties as stated were determined under controlled laboratory conditions. This data sheet may be updated without notice. Please ensure you have the latest copy. If you are a customer, then any contract with you is in accordance with our latest terms and conditions, which are available to download from our website. Where goods are acquired for business purposes, Parts 1 to 4 of the Consumers Guarantee Act 1993 will not apply. To the maximum extent permitted by law, we have no liability (whether statutory, in contract or tort, including negligence) to buyers, users or specifiers of our products for any physical, direct or indirect damage, economic loss or any other loss or costs caused or contributed by us or any of our agents or employees in respect of any goods or services supplied. Also to the maximum extent permitted by law, all conditions and warranties expressed or implied by statute or common law, equity, trade custom or usage or otherwise howsoever are excluded. If, notwithstanding the foregoing, Stratmore Construction Solutions Limited is found to have any liability, then it is agreed that the liability is nevertheless limited to the price of the relevant goods or services purchased from us.

