

# CONCRETE DISSOLVER

# STRIPCRETE

---

## TECHNICAL DATA

---

### 1.0 DESCRIPTION

Stripcrete is biodegradable solution designed to soften and easily remove concrete or cement residues from tools or concrete placing equipment. It eliminates the need for hammering, sand blasting or chipping to remove old concrete residues.

### 2.0 PHYSICAL PROPERTIES:

2.1	SOLUBILITY	Soluble in water
2.2	VAPOUR DENSITY (Air = 1)	Water
2.3	BOILING POINT IN DEGS C	Approx 100
2.4	SPECIFIC GRAVITY	1.1
2.5	pH	<2
2.6	VISCOSITY	Liquid
2.7	APPEARANCE AND ODOUR	Pale yellow, pungent liquid.
2.8	COVERAGE	Dependent on concrete and cement residue thickness

### 3.0 USES

- 3.1 Stripcrete is used to remove concrete or cement residues from tools or concrete placing equipment or other similar surfaces.

### 4.0 APPLICATION INSTRUCTIONS

- 4.1 Wear protective gloves and eye protection when using this product. Use only outdoors or in a well-ventilated area. Stripcrete works best on DRY concrete residues. Do not wet down tools before or during application. Do not thin down solution. Do not work under direct sunlight as the heat causes the solution to evaporate and lose proper dissolving and softening action.
- 4.2 Apply from a spray bottle or brush direct to the concrete and allow about 30 minutes or so before scraping off the softened layer of old concrete. The concrete surface must be completely saturated - this is MOST IMPORTANT. If needed a second application can be made after 30 minutes. The solution will foam a little during the softening action; this is normal and indicates the product is working. If the treated area dries out and becomes white DO NOT WET DOWN WITH WATER. Apply more Stripcrete and allow this to act for 10 – 30 minutes before removing the soft residue. High pressure water blasters can be used after the final application. If the concrete to be removed is a thick layer (more than 6mm) two applications over 24 hours may be required. After the softened material is removed the tools should be thoroughly washed with water.

# STRIPCRETE

---

## TECHNICAL DATA Continued

---

### 5.0 PRECAUTIONS

Wear protective equipment as detailed – eye and skin protection.

Store locked up when not in use. Do not transfer this product to another container; use only the original supplied container.

Read Safety Data Sheet and labels before handling and using this product.

All concrete floors and driveways should be protected from spillage or contact with Stripcrete. Stripcrete should not affect painted surfaces and plastics but contact should either be avoided or tested before use if anticipated. Contact with some metals or alloys can cause changes in colour and may require wet and dry sanding to remove stains.

DO NOT allow runoff (including dissolved material) to enter drains, waterways, streams, etc. Dispose of dissolved material in accordance with local regulations regarding concrete/cement residue.

### 6.0 PACKAGING

4-litre and 20-litre containers.



Leading solutions for construction.

The information contained in this data sheet, is to the best of our knowledge accurate and any recommendations or suggestions which may be made are without liability on our part, since the conditions of use are beyond our control. Users are urged to make their own assessment of our products under their own conditions and for their own requirements. Stratmore Construction Solutions Limited reserves the right to alter formulations without notice. Properties as stated were determined under controlled laboratory conditions. This data sheet may be updated without notice. Please ensure you have the latest copy. If you are a customer, then any contract with you is in accordance with our latest terms and conditions, which are available to download from our website. Where goods are acquired for business purposes, Parts 1 to 4 of the Consumers Guarantee Act 1993 will not apply. To the maximum extent permitted by law, we have no liability (whether statutory, in contract or tort, including negligence) to buyers, users or specifiers of our products for any physical, direct or indirect damage, economic loss or any other loss or costs caused or contributed by us or any of our agents or employees in respect of any goods or services supplied. Also to the maximum extent permitted by law, all conditions and warranties expressed or implied by statute or common law, equity, trade custom or usage or otherwise howsoever are excluded. If, notwithstanding the foregoing, Stratmore Construction Solutions Limited is found to have any liability, then it is agreed that the liability is nevertheless limited to the price of the relevant goods or services purchased from us.

