

High Strength Paint Remover

TEXOL

TECHNICAL DATA

1.0 DESCRIPTION

TEXOL is a non-flammable, highly effective paint remover, with excellent adhesion to vertical surfaces. TEXOL is suitable for brush or spray application to most acrylics, enamels, varnishes as well as many other coatings. TEXOL will not attack wood or metals. It is also suitable for use on many epoxy esters, epoxy amides and stoved finishes. Does not contain Phenols.

2.0 PROPERTIES

2.1. Colour	Opaque White.
2.2. Specific Gravity	1.20
2.3. Flash Point	Non-Flammable
2.4. Viscosity	Smooth, paste-like.
2.5. Toxicity	Poisonous
2.6. DG Classification	6.1
2.7. Shelf Life	One year in original, unopened container.

3.0 USES

TEXOL is used to strip paint from a variety of surfaces. It can also be used to remove other similar coatings.

4.0 APPLICATION INSTRUCTIONS

See PRECAUTIONS before use. Read label before use.

- 4.1. Apply TEXOL by brush or spray to the paint to be removed.
- 4.2. TEXOL may be applied to vertical or inclined surfaces due to its thixotropic properties.
- 4.3. Use masking tape to protect untreated surfaces. Allow to soak onto surface and soften the coating, but do not allow to dry out (some surfaces may require longer contact periods and/or thicker coats of TEXOL).
- 4.4. Coverage is dependent on the type of paint to be removed, the surface texture of the painted surface and the number of coats.
- 4.5. Remove paint with scraper or hose before the TEXOL/paint begins to dry and harden.
- 4.6. Repeat where necessary (after allowing surface to dry).
- 4.7. Wash equipment in water and detergent.

TEXOL

TECHNICAL DATA Continued

5.0 PRECAUTIONS

Wear full skin protection, including face shield, nitrile or similar gloves and overalls. Do not use in confined space without adequate ventilation. Do not smoke during use. If TEXOL contacts skin, wash off with soap and water. Refer Material Safety Data Sheet for complete information.

Open lid or cap of container slowly (away from face) to allow any built-up pressure to reduce.

Lead based paint that has been removed from the surface must be disposed of in accordance with local or national regulations.

Store with lid tightly closed and in a secure area.

6.0 PACKAGING

4-litre cans.

20-litre pails.

200-litre drums.



Leading solutions for construction.

The information contained in this data sheet, is to the best of our knowledge accurate and any recommendations or suggestions which may be made are without liability on our part, since the conditions of use are beyond our control. Users are urged to make their own assessment of our products under their own conditions and for their own requirements. Stratmore Construction Solutions Limited reserves the right to alter formulations without notice. Properties as stated were determined under controlled laboratory conditions. This data sheet may be updated without notice. Please ensure you have the latest copy. If you are a customer, then any contract with you is in accordance with our latest terms and conditions, which are available to download from our website. Where goods are acquired for business purposes, Parts 1 to 4 of the Consumers Guarantee Act 1993 will not apply. To the maximum extent permitted by law, we have no liability (whether statutory, in contract or tort, including negligence) to buyers, users or specifiers of our products for any physical, direct or indirect damage, economic loss or any other loss or costs caused or contributed by us or any of our agents or employees in respect of any goods or services supplied. Also to the maximum extent permitted by law, all conditions and warranties expressed or implied by statute or common law, equity, trade custom or usage or otherwise howsoever are excluded. If, notwithstanding the foregoing, Stratmore Construction Solutions Limited is found to have any liability, then it is agreed that the liability is nevertheless limited to the price of the relevant goods or services purchased from us.